

TSCOM TP1006

COST-EFFECTIVE GEAPON CUSTOMER PREMISE DEVICE

Integrated With 4-Port 10/100 Base-T Switch, 2 FXS Port Delivers High Speed Data Services Over Gigabit Ethernet Passive Network(Gepon)



- **Full IEEE802.3/802.3ah Compliance**
- **Compact Chassis**
- **64 Splits, 30Km Reach**
- **Service Supported:**
VOIP, IP Video And Data
- **Multiple Subscriber/ Multiple Service Support from Single ONU**
- **Individualized Billing Per Service Level Agreement**
- **Port Aggregation And Spanning-Tree Support For Redundant Data Network Access**
- **Vlan Managed Services With Priority QOS Processing**
- **Multicast Support For Video Streaming**
- **Remote Provisioning And Management**
- **Advanced Security**
- **Circuit Testing And Loop Backs For Telephony Services**

ONU TP1006 provides four 10/100M Base-T Ethernet ports with advanced L2 functionality for Data and IPTV video services. The ONU TP1006 is configured and managed remotely via Telesail product family (OLT). TP1006 ONU also provides two FXS Voice over IP (VoIP) ports for voice communications. In typical CPE devices, VoIP communications are provided via VoIP protocol with FXS ports.

It is suited for residential and SOHO markets, providing an uplink to the central office through its GEAPON port, and a downlink to the individual residential user or SOHO through four Ethernet ports and two VoIP ports. The product provides comprehensive L2 switching, QoS and Security Features for SOHO Applications and is a cost effective solution enabling FTTH. ONU TP1006 delivers high rate data and IPTV over a single fiber. A future-proof, Fiber To The Home (FTTH) solution, the ONU TP1006 is a critical element in the successful delivery of multimedia video, voice and data over a single optical fiber.

KEY BENEFITS

- Full IEEE 802.3/802.3ah compliance
- Services supported: VOIP, IP Video and Data
- Wire-speed Layer 2 switch, in full bidirectional data rate on each port
- "Plug-and-play" via auto-discovery and configuration
- Multiple subscriber/Multiple services support from single ONU
- Hardware efficiency: Multiple services from any Ethernet port
- IGMP Snooping, Multicast VLAN, Port isolation
- 8K MAC address table, 255 VLAN entries
- Support 802.1d STP, 802.1w RSTP
- Secure access via Access Control List (ACL) on L2-L7
- IEEE 802.3x flow control for full-duplex, back pressure for half-duplex
- Advanced QoS functions enable billing by Service Level Agreement
- Integrated VOIP functionality: supports MGCP, SIP, H.323
- Remote management with facilitates activation and diagnostics, advanced OAM functions
- Quick installation and turn-up via pre-provisioning of the ONU
- Flexible installation, long reach operation range, temperature hardened design
- Standards compliant

Specification

Physical

- Dimensions
206 mm(W) x 135.5 mm (D) x 41.8 mm(H)
- Weight: <0.5kg
- Desktop mount

Power and Environmental

- Power Consumption:<10W
- Power
AC: 100~240VAC,47~63Hz
- Operating Requirement
-5°C to +45°C ambient air temperature
5% to 95% operating humidity
(non condensing)
- Storage Requirement
-20°C to +70°C ambient air temperature
5% to 95% humidity
(non condensing)

Architecture

- Compact chassis
- 1 fix ONU EPON interface
- 4 10/100M Base-T interface
- 2 RJ-11 FXS port

Optical Characteristics

- IEEE 802.3ah compliant
- SFF optical module
- SC/PC optical PHY (single-mode fiber)
- Tx:1310nm Rx:1490nm
- Symmetric 1.25Gbps per PON port
- 20km distance
- Splits per OLT port Max: 1:64
- Tx Power:+0dbm ~ +4dbm
- Rx Sensitivity:-26dbm

Layer 2 switching Functions

- STP/RSTP
- Port based Vlan,IEEE802.1Q with 4K VLANs handling
- VLAN Stacking(QinQ),selective QinQ
- IEEE 802.3ad link aggregation(LACP)
- IEEE802.3x in full duplex, back pressure in half duplex,Head of Line
- 8K MAC table support
- MAC management(Learning control, limit and aging) support
- EAPS loop circuit protection
- Ethernet – II, Ethernet-SNAP

Multicast

- IGMPv1/v2/v3, IGMP Snooping
- Multicast Vlan,Fast Leave
- Multicast control support

Network Security

- Access Control List (ACL)
- Port/MAC binding,MAC filtering and Limit
- Per VLAN User Isolation
- Packet mirroring per ingress/egress port
- Limiting the maximum number of users per port
- EPON Frame Encryption: AES128 bit downlink encryption
- Broadcast/Multicast/DLF storm control
- Dying-Gasp

Voice

- Support SIP/MGCP
- Codec support: G.711 a/μ law, G.729,G.726. G.723 etc
- 3-way conference , Call Forward ,Call Hold ,Call Waiting ,Call Transfer

Quality of Service (QoS)

- 4 CoS queuing
- IEEE 802.1 p and DSCP PRI Mark/remark
- SP and WRR congestion management
- Classification based Traffic Metering, Shaping and Marking
- CAR

Management

- Web-enabled GUI based local configuration
- FTP/TFTP,Telnet,Console interface with CLI
- RMONv1, group 1, group 2, group 3 and group 9
- SSHv1/v2
- ONU Remote Upgrade and Management
- Environmental monitoring
- Local or the server's syslog log

Safety Compliance

- CE marking
- FCC Class A
- ROHS5,CCC
- VCCI Class B
- EN 60950-1
UL 60950-1

Order Information

TSCOM TP1006 - ONU

TP1006	GEPON optical network unit provides 1 fix EPON interfaces, 4 10/100M BaseT ,2 RJ11 interface,single power supply ,AC110-240V, Plastic case
--------	--

Telesail Technology Co., Ltd

3F,TAIWEI Tower, No. 31 Jiancai West St.
Haidian District, Beijing, China 100096
Email : sale@telesail.com
Tel: +86 10 8291 2638
Fax: +86 10 5141 7010
Web Site: http://www.telesail.com

About Telesail Technology Co., Ltd

Telesail Technology is professional in IP-based, end-to-end networking solutions and international service and support. The company sells its broadband, wireless,transmission solutions to operators in both emerging and established telecommunications markets around the world. Telesail enables its customers to rapidly deploy revenue-generating access services using their existing infrastructure, while providing a migration path to cost-efficient, end-to-end IP networks.

For more information about Telesail, visit the company's Web site at <http://www.telesail.com>